


Packo High Shear Pump

enhances productivity up to 100%!



PATENTED DESIGN

- Self pumping
- Hygienic design, so easy to clean
- Easy installation and maintenance
- Use of std. components
- Highest efficiency on the market, 50% less energy consumption
- Very quiet operation

Shear Mixer Pump Series SFP2 & SFP3

Working principle

The new, efficient high shear mixing method is based on the proven EHEDG certified pump series FP2 with open impeller and series FP3 with closed impeller.


The Packo shear mixer pump is mainly used for in-line mixing, homogenisation and dispersion applications.

The shear is generated between the rotor and an innovative and optimized perforated stator (patented design).

The shear can be optimized and increased by raising the speed of rotation. Shear rates up to 100.000 s⁻¹ can be achieved at a maximum speed of 3600 rpm!

The final goal is to achieve a homogeneous solution of two liquids with high difference in viscosity and/or density and to obtain a particle size reduction for emulsions and particles.

The smooth operational performance achieved by this conforms with the unique precision and quality you have come to expect from all Packo components.



The stator



Thanks to the special designed stator (patented design) together with small clearance between rotor and stator an important shear will be generated resulting in a significant particle size reduction (between 1.4 and 2 μm)! A smaller particle size will result in a more stable final product!



Particle Size Reduction

Particle size from a customer trial with a dairy based formulation with 3.5% AMF.

Sample test externally by 3rd party on a Malverne instrument using Laser diffraction.



Types

• SFP2/32-160	35 m ³ /h	2.5 bar	max. 11 kW	max. 750 cP	shear up to 30.000 s ⁻¹
• SFP2/40-160	50 m ³ /h	2.5 bar	max. 11 kW	max. 750 cP	shear up to 30.000 s ⁻¹
• SFP2/50-160	75 m ³ /h	2.5 bar	max 11 kW	max. 750 cP	shear up to 30.000 s ⁻¹
• SFP2/40-250	50 m ³ /h	4 bar	max. 22 kW	max. 750 cP	shear up to 100.000 s ⁻¹
• SFP3/80-160	130 m ³ /h	2.0 bar	max. 22 kW	max. 1000 cP	shear up to 30.000 s ⁻¹
• SFP3/100-200	200 m ³ /h	5.0 bar	max. 45 kW	max. 1000 cP	shear up to 40.000 s ⁻¹

Typical applications

Mixing of 2 liquids

- with a large different specific gravity (f.i. honey in water)
- having a large different viscosity (f.i. oil in butter)
- that are difficult to mix (f.i. oil in water)

Dispersing of solids in liquids
(f.i. toothpaste in water)

Dispersion of gas in liquids
(foamed desserts)

Dairy

- Recombined milk
- Drink yoghurt

Beverage

- Soda syrups & concentrate
- Sucrose solution
- Green tea

Food

- Hummus
- Salsa & hot sauce
- Fruit puree

Personal Care

- Shampoo & conditioner
- Sanitizer gel

Bio-pharm


- Media prep
- Buffer solution
- Glucose

Industrial

- Paintballs
- Edible oil refining
- Pigment dispersion

The right solution for every requirement!

Performance SFP2 & SFP3



The benefits

Packo High Shear Pump Series SFP2 & SFP3

- High efficient so less energy cost!
- Use of std. components, easy maintenance
- Several seal configurations available
- ATEX available
- Monobloc execution, easy installation
- Easy to clean (CIP and SIP)
- 'Self' pumping
- High mechanical & hydraulic shear
- Rapid solid dissolving

Particle size reduction leading to a stable product!



For complete mixing & homogenizing units, please contact Packo Pumps.

A **VERDER** COMPANY



BQA_QMS019_C_1994041



BQA_EMS019_C_2015041

Production in Belgium
in an ISO 9001 and ISO 14001
certified company.

Packo
Pumps

We optimize your flow

Packo Pumps Belgium
Industriepark Heernisse
Cardijnlaan 10
8600 Diksmuide BE
Tel. +32 51 51 92 80
Fax +32 51 51 92 99
pumps@packo.com
www.packopumps.com