


# Pump series CRP




## Characteristics

The pumps of the CRP series are perfectly cleanable EHEDG certified air handling pumps and are mainly used to pump a mixture of liquid and air. Constructed in thick cold rolled plate, 100% non-porous and extremely smooth. The pumps have open or closed investment cast impellers, constructed in 316L or duplex materials. Thanks to its crevice-free design and electropolishing as a final surface treatment, the CRP pump series are perfectly cleanable, resulting in a reliable component for your production process.



### CRP

- 1 Electropolished, easy to clean construction, no bacteria traps and no small clearances in order to clean the area around the O-ring
- 2 Unique air handling design with cleanable air separator
- 3 By-pass to casing taking care about air evacuation
- 4 Monobloc execution with std. IEC motors
- 5 Standardized mechanical seals to EN 12756 FDA approved bellow mechanical seals or sterile O-ring seals (spring not in contact with the liquid)
- 6 One mechanical seal diameter: 33 mm, except for 80-160: Ø 43 mm



## Your benefits

- Higher pump efficiency compared with a classic liquid ring pump
- Low NPSH values: less risk on cavitation
- Electropolished: perfectly cleanable
- Easy construction and easy maintenance: less downtime
- Construction without non-return valve
- Easy to install
- 2 mechanical seal diameters for the entire range
- Robust construction
- Limited noise level

## Application areas

Thanks to its unique air handling design based on a standard centrifugal pump, the CRP series are particularly suitable as a CIP return pump, as well as for unloading applications.

They are used in the most demanding hygienic applications in almost all industries such as dairies, breweries, beverage industry, distilleries, etc.

Pump series	CRP
<b>Performance</b>	
max. flow rate	120 m <sup>3</sup> /h
max. differential head	75 m
max. inlet pressure	10 bar
max. liquid viscosity	10 cP
max. temperature	140°C
impeller type	open or closed
max. free passage	22 mm
max. motor power	22 kW
max. speed	3000/3600 rpm
available frequency	50/60 Hz
<b>Technical specifications</b>	
materials wetted parts	stainless steel 316L or similar
mechanical seal configuration	single bellow, sterile, quench, double
available material o-ring	EPDM, FKM, FEP-FKM, FFKM or similar
connections	hygienic fittings only
surface finish	hygienic quality, internal welds hand polished + electropolished (casing: 0.8 µm + impeller: 3.2 µm)
certificates & legislation	

## Performance curves at 2900 rpm

